



## SUPER-SFER

# 1621



Kugelhahn mit vollem Durchgang, IG/AG, mit Aluminium Flügelgriff.

## Technische Spezifikationen



| GRÖSSE | DN | BOX | MASTER BOX | CODE       | I    | L    | ØH   | CH | M  | H    | KV   | PN | KG   |
|--------|----|-----|------------|------------|------|------|------|----|----|------|------|----|------|
| 1/4"   | 8  | 20  | 80         | 1721020000 | 11   | 59   | 23   | 20 | 50 | 37,5 | 5,4  | 64 | 0,13 |
| 3/8"   | 10 | 20  | 80         | 1721030000 | 11,4 | 59,5 | 23   | 20 | 50 | 37,5 | 6    | 64 | 0,13 |
| 1/2"   | 15 | 20  | 80         | 1621040000 | 15   | 68,7 | 30   | 25 | 50 | 48,5 | 16,3 | 50 | 0,20 |
| 3/4"   | 20 | 10  | 40         | 1621050000 | 16,3 | 78   | 36   | 31 | 64 | 59,5 | 29,5 | 40 | 0,31 |
| 1"     | 25 | 10  | 20         | 1621060000 | 19,1 | 92,2 | 43,5 | 38 | 64 | 59,5 | 29,5 | 40 | 0,31 |

Temperature range: -20°C +160°C.

\*Art. [1721](#)

# Anwendungen



DRINKING  
WATER



HEATING



HVAC



COMPRESSED  
AIR



INDUSTRIAL



MARINE