


1520



Full bore ball valve, F/F threaded, with aluminium T-handle.

Technical specifications



| SIZE | DN | BOX | MASTER BOX | CODE | I | L | ØH | CH | M | H | KV | PN | KG |
|-------|----|-----|------------|------------|------|------|------|----|----|------|------|----|------|
| 1/4** | 8 | 20 | 80 | 1720020000 | 11 | 51,5 | 23 | 20 | 50 | 37,5 | 5,4 | 64 | 0,14 |
| 3/8** | 10 | 20 | 80 | 1720030000 | 11,4 | 51,5 | 23 | 20 | 50 | 37,5 | 6 | 64 | 0,12 |
| 1/2" | 15 | 20 | 80 | 1520040000 | 12 | 47,5 | 30 | 25 | 50 | 39,5 | 15,7 | 50 | 0,14 |
| 3/4" | 20 | 10 | 40 | 1520050000 | 12 | 53 | 36 | 31 | 64 | 50,5 | 28 | 40 | 0,23 |
| 1" | 25 | 10 | 20 | 1520060000 | 14,5 | 65,5 | 43,5 | 38 | 64 | 53 | 41,5 | 40 | 0,35 |

Temperature range: -20°C +160°C.

*Art. [1720](#)

Applications



DRINKING
WATER



HEATING



HVAC



COMPRESSED
AIR



INDUSTRIAL



MARINE