


EUROBLOCK


100001

PATENTED



Válvula de retención a paso total, roscas hembra/hembra, asiento en **Viton®** por aplicaciones con hidrocarburos no halogenados o carburantes (gasolina, kerosén...).

Especificaciones técnicas



TAMAÑO	DN	BOX	MASTER BOX	CÓDIGO	I	CH	ØB	ØC	A	KV	PN	KG
3/8"	10	20	160	10000103	11,4	21	20	27	47	1,8	40	0,08
1/2"	15	15	120	10000104	15	26	25	34,5	59	7,9	40	0,14
3/4"	20	10	80	10000105	16,3	32	31	42	65	13	40	0,21
1"	25	10	40	10000106	19,1	39	38	49	75	19	25	0,33
1"1/4	32	6	24	10000107	21,4	49	48	61	83,5	29,5	25	0,55
1"1/2	40	4	16	10000108	21,4	55	54	73	89	44,6	16	0,76
2"	50	2	8	10000110	25,7	68	67	87,5	101,5	61,3	16	1,15
2"1/2	65	2	4	10000112	30,2	83	83	111,5	121	77,5	16	2,13
3"	80	2	4	10000114	33,3	98	98	133	136	121,9	16	3,30
4"	100	-	2	10000118	39,3	128	127	163	159	189,8	16	5,85

Temperature range: -10°C +150°C.

Aplicaciones



DRINKING
WATER