


1810

Valvola a sfera a passaggio totale, filettatura F/F, con leva in acciaio.

Specifiche tecniche



MISURA	DN	BOX	MASTER BOX	CODICE	ØP	I	L	ØH	CH	R	H	KV	PN	KG
1/4**	8	20	80	1710020000	10	11	51,5	23	20	95	43	5,4	64	0,15
3/8**	10	20	80	1710030000	10	11,4	51,5	23	20	95	43	6	64	0,14
1/2"	15	20	80	1810040000	15	13,5	55	33	25	96	47	16,3	64	0,20
3/4"	20	10	40	1810050000	20	12,5	57,5	39	31	120	59	29,5	50	0,26
1"	25	10	20	1810060000	25	15	69,5	49	38	120	63	43	50	0,49
1"1/4	32	6	12	1810070000	32	17	81,5	59	48	150	76,5	89	50	0,81
1"1/2	40	4	8	1810080000	40	18	95	73	54	150	82,5	230	40	1,17
2"	50	2	4	1810100000	50	22	113	87	67	160	95	265	40	1,87
2"1/2*	65	2	4	1710120000	65	30,2	152	111	90	206	123	540	25	3,73
3**	80	0	4	1710140000	80	33,3	177	136	105	206	133	873	25	5,95
4**	100	0	2	1710180000	100	39,3	214	166	130	261	165	1390	25	10,57

Limiti di temperatura: -20°C +160°C.

*Art. [1710](#)

Applicazioni



DRINKING
WATER



HEATING



HVAC



COMPRESSED
AIR



INDUSTRIAL



MARINE